

Page 1 of 2
Declaration of Performance
Reference: DoP01CMFS018
Edition nr 1.0



## **Declaration of Performance**

Conforming Regulation (EU) No 305/2011 Annex III
Construction Products Regulation

## **Quartzline Cementitious FS**

DoP01CMFS018

EN 13813:2002

1. Product Type Quartzline Cementitious FS

Unique identification code of the product-type:

2. Type Cementitious FS batch or serial number or any other element allowing batch no. refer to packaging

identification of the construction product as required under Article 11(4):

3. Intended use Cementitious mortar for indoor use or uses of the construction product, in accordance with EN13813: CT - C30 - F6 - A22

or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

4. Name, registered trade name
 Ouartzline BV
 Daltonstraat 54
 manufacturer as required under Article 11(5):
 3316GD Dordrecht, The Netherlands

5. Contact Address: Not relevant (see 4)

Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

**6. AVCP:** System or systems of assessment and **System 4** verification of constancy of performance (AVCP) of the

construction product as set out in CPR, Annex V:

7. Notified body (hEN): Not relevant
In case of the declaration of performance (DoP)concerning

8. Notified body (ETA) Not relevant

In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:

a construction product covered by a harmonised standard:

Quartzline B.V., W.A. Boogaerdtstraat 5, NL-3316 BN Dordrecht, The Netherlands, English Edition 1.0 (01-2018) Tel +31 78 6 513100 Fax +31 78 6177390 , http://www.quartzline.nl



## 9. Declared performance

Essential	Characteristics	Performance Test Standard	Harmonised technical Specification
Release of corrosive	СТ	EN 13813	
Substances			
Abrasion Resistance:	≤ A22 ¹)	EN 13892-5	
Compression strength:	C30	EN 13892-2	
Tensile strength:	F6	EN 13892-2	
Sound insulation:	NPD <sup>2)</sup>	EN ISO 140-1	EN 13813
Sound absorption:	NPD	EN ISO 354	
Reaction to fire:	E <sub>fl</sub> <sup>3)</sup>	EN 13501-1	
Permeability to water vapour:	NPD	EN ISO 7783-1	
Thermal resistance:	NPD	EN 12664	
Chemical resistance:	NPD	EN 13529	

<sup>1)</sup> Minimum Classification

<sup>3)</sup> According to Commission Decision 2010/85/EU of 9 February 2010 the product fulfils the reaction-to-fire performance class E/Efl without further testing



## 10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Peter Groeneweg
Research and development

Dordrecht, 30 January 2018

Willem van der Marel Quality Control

Quartzline B.V., W.A. Boogaerdtstraat 5, NL-3316 BN Dordrecht, The Netherlands, English Edition 1.0 (01-2018) Tel +31 78 6 513100 Fax +31 78 6177390 , http://www.quartzline.nl

<sup>2)</sup> No Performance Determined