

Page 1 of 2
Declaration of Performance
Reference: DoP01PRUN018
Edition nr 1.0

## **Declaration of Performance**

Conforming Regulation (EU) No 305/2011 Annex III
Construction Products Regulation

## **Quartzline Primer Universal**

DoP01PRUN018

EN 13813:2002

1. Product Type

Unique identification code of the product-type:

2. Type

batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

3. Intended use

or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

4. Name, registered trade name

or registered trade mark and contact address of the manufacturer as required under Article 11(5):

5. Contact Address:

Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

6. AVCP:

System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:

7. Notified body (hEN):

In case of the declaration of performance (DoP)concerning a construction product covered by a harmonised standard:

8. Notified body (ETA)

In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:

**Quartzline Primer Universal** 

Primer Universal batch no. refer to packaging

1-Component waterbased acrylillic primer

EN13813: SR-B1,5

Quartzline BV
Daltonstraat 54
3316GD Dordrecht, The Netherlands

Not relevant (see 4)

System 4

Not relevant

Not relevant

Quartzline B.V., W.A. Boogaerdtstraat 5, NL-3316 BN Dordrecht, The Netherlands, English Edition 1.0 (01-2018) Tel +31 78 6 513100 Fax +31 78 6177390 , http://www.quartzline.nl



## 9. Declared performance

Essential	Characteristics	Performance Test Standard	Harmonised technical Specification
Release of corrosive Substances	SR	EN 13813	
Abrasion Resistance:	NPD 1)	EN 13892-4	
Bond strength:	≥ B1,5	EN 13892-8	
Impact resistance:	NPD	EN ISO 6272	
Sound insulation:	NPD	EN ISO 140-1	EN 13813
Sound absorption:	NPD	EN ISO 354	
Reaction to fire:	E <sub>fl</sub> <sup>2)</sup>	EN 13501-1	
Permeability to water vapour:	NPD	EN ISO 7783-1	
Thermal resistance:	NPD	EN 12664	
Chemical resistance:	NPD	EN 13529	

- 1) No Performance Determined
- 2) According to Commission Decision 2010/85/EU of 9 February 2010 the product fulfils the reaction-to-fire performance class E/Efl without further testing



## 10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Dordrecht, 30 January 2018

Peter Groeneweg
Research and development

Questaline

Willem van der Marel Quality Control

Quartzline B.V., W.A. Boogaerdtstraat 5, NL-3316 BN Dordrecht, The Netherlands, English Edition 1.0 (01-2018) Tel +31 78 6 513100 Fax +31 78 6177390 , http://www.quartzline.nl