

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Topcoat E B-component
Product group : Coatings and paints, fillers, putties, thinners

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use
Function or use category : Coating

1.2.2. Uses advised against

No additional information available.

1.3. Details of the supplier of the safety data sheet

Quartzline BV
W.A. Boogaerdstraat 5
3316 BN Dordrecht - Nederland
T +31 (0)78 6513100 - F +31 (0)78 6177390
info@quartzline.nl - www.quartzline.nl

1.4. Emergency telephone number

Emergency number : +31 (0)78 6513100
This number is serviced during office hours.

Country	Official advisory body	Address	Emergency number	Remark
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA Belfast	0344 892 0111	Only for the purpose of informing medical personnel in cases of acute intoxications

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4 H302
Acute toxicity (inhalation:dust,mist) Category 4 H332
Skin corrosion/irritation, Category 1, Sub-Category 1B H314
Serious eye damage/eye irritation, Category 1 H318
Skin sensitisation, Category 1 H317
Reproductive toxicity, Category 2 H361d
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412
Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects

Causes severe skin burns and eye damage. May cause an allergic skin reaction. Harmful if inhaled. Harmful if swallowed. Suspected of damaging fertility or the unborn child. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Contains

Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer; m-phenylenebis(methylamine); 3-aminomethyl-3,5,5-trimethylcyclohexylamine; salicylic acid

Topcoat E B-component

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

Hazard statements (CLP)	: H302+H332 - Harmful if swallowed or if inhaled. H314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction. H361d - Suspected of damaging the unborn child. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P201 - Obtain special instructions before use. P261 - Avoid breathing vapours, mist. P280 - Wear protective clothing, protective gloves, eye protection. P303+P361+P353+P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.. Immediately call a doctor, a POISON CENTER. P305+P351+P338+P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER. P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc. (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
benzyl alcohol	(CAS-No.) 100-51-6 (EC-No.) 202-859-9 (EC Index-No.) 603-057-00-5 (REACH-no) 01-2119492630-38	25 – 50	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319
Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer	(CAS-No.) 68609-08-5 (EC-No.) 614-657-1 (REACH-no) 01-2120106013-80	25 – 50	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317 Aquatic Chronic 2, H411
m-phenylenebis(methylamine)	(CAS-No.) 1477-55-0 (EC-No.) 216-032-5 (REACH-no) 01-2119480150-50	10 – 25	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412
3-aminomethyl-3,5,5-trimethylcyclohexylamine	(CAS-No.) 2855-13-2 (EC-No.) 220-666-8 (EC Index-No.) 612-067-00-9 (REACH-no) 01-2119514687-32	10 – 25	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Skin Sens. 1A, H317 Aquatic Chronic 3, H412
salicylic acid	(CAS-No.) 69-72-7 (EC-No.) 200-712-3 (EC Index-No.) 607-732-00-5 (REACH-no) 01-2119486984-17	2 – 10	Repr. 2, H361d Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Take off immediately all contaminated clothing. Rinse skin with water/shower. Get immediate medical advice/attention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Get immediate medical advice/attention.

Topcoat E B-component

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Presents no particular fire or explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon oxides (CO, CO ₂).

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe vapours, mist.
----------------------	--------------------------------------------------------------------------------------------

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Do not breathe vapours, mist. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep only in the original container in a cool well ventilated place. Keep container closed when not in use. Store locked up. Keep out of frost.
Incompatible products	: Strong oxidation agent.
Heat and ignition sources	: Keep away from heat and direct sunlight.

7.3. Specific end use(s)

No additional information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available.

8.1.2. Recommended monitoring procedures

No additional information available.

Topcoat E B-component

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

8.1.3. Air contaminants formed

No additional information available.

8.1.4. DNEL and PNEC

No additional information available.

8.1.5. Control banding

No additional information available.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

protective clothing. Gloves. Safety glasses. Insufficient ventilation: wear respiratory protection.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses. Standard EN 166 - Personal eye-protection - specifications

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing. CEN : EN 340; EN 369; EN 465

Hand protection:

Wear suitable gloves resistant to chemical penetration. Chemical resistant gloves (according to European standard NF EN 374 or equivalent).

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Gloves	Nitrile rubber (NBR), Viton	6 (> 480 minutes)	≥0.5		EN 374

8.2.2.3. Respiratory protection

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. EN 143

Device	Filter type	Condition	Standard
Breathing apparatus	Type A - High-boiling (>65 °C) organic compounds, Type P2	Vapour protection, Protection for Liquid particles	EN 143

8.2.2.4. Thermal hazards

No additional information available.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

When using do not eat, drink or smoke.

Topcoat E B-component

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: yellowish.
Odour	: Amine-like.
Odour threshold	: No data available.
pH	: No data available.
Relative evaporation rate (butylacetate=1)	: No data available.
Melting point	: No data available.
Freezing point	: No data available.
Boiling point	: > 200 °C
Flash point	: > 100 °C (DIN 53213)
Auto-ignition temperature	: 380 °C
Decomposition temperature	: No data available.
Flammability (solid, gas)	: No data available.
Vapour pressure	: 0.1 hPa (20 °C)
Relative vapour density at 20 °C	: No data available.
Relative density	: No data available.
Density	: 1.05 g/cm ³ (23 °C; ISO 2811-2)
Solubility	: Water: Practically not miscible
Partition coefficient n-octanol/water (Log Pow)	: No data available.
Viscosity, kinematic	: 323.81 mm ² /s
Viscosity, dynamic	: 340 mPa·s (20 °C; ISO 3219)
Explosive properties	: No data available.
Oxidising properties	: No data available.
Lower explosive limit (LEL)	: 1.2 vol %
Upper explosive limit (UEL)	: 13 vol %

9.2. Other information

No additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong oxidation agent.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Harmful if inhaled.

Topcoat E B-component	
ATE oral	500 mg/kg bodyweight
ATE dust/mist	2 mg/l/4h

benzyl alcohol (100-51-6)	
LD50 oral rat	1620 mg/kg
ATE oral	1620 mg/kg bodyweight

Topcoat E B-component

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

ATE gases	4500 ppmv/4h
ATE vapours	11 mg/l/4h
ATE dust/mist	1.5 mg/l/4h

Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer (68609-08-5)

LD50 dermal rat	> 2000 mg/kg
ATE oral	500 mg/kg bodyweight

m-phenylenebis(methylamine) (1477-55-0)

LD50 dermal rat	> 3100 mg/kg
LC50 Inhalation - Rat	≈ 1.34 mg/l/4h
ATE oral	500 mg/kg bodyweight
ATE gases	4500 ppmv/4h
ATE vapours	11 mg/l/4h
ATE dust/mist	1.5 mg/l/4h

3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)

LD50 oral rat	1030 mg/kg
LD50 dermal rabbit	1340 mg/kg
ATE oral	1030 mg/kg bodyweight
ATE dermal	1340 mg/kg bodyweight

salicylic acid (69-72-7)

LD50 oral rat	891 mg/kg
LD50 dermal rat	> 2000 mg/kg
ATE oral	891 mg/kg bodyweight

Skin corrosion/irritation	: Causes severe skin burns.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging the unborn child.
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

Topcoat E B-component

Viscosity, kinematic	323.81 mm ² /s
----------------------	---------------------------

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

Topcoat E B-component

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

benzyl alcohol (100-51-6)

LC50 - Fish [1]	460 mg/l (Pimephales promelas)
EC50 - Crustacea [1]	230 mg/l (OECD 202; Daphnia magna)
ErC50 algae	770 mg/l (OECD 201; Pseudokirchneriella subcapitata)
NOEC chronic crustacea	51 mg/l (OECD 211; Daphnia magna)
NOEC chronic algae	310 mg/l (OECD 201; Pseudokirchneriella subcapitata)

Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer (68609-08-5)

LC50 - Fish [1]	1.62 mg/l (OECD 203; Danio rerio)
EC50 - Crustacea [1]	1.59 mg/l (OECD 202; Daphnia magna)
ErC50 algae	3.13 mg/l (OECD 201; Pseudokirchneriella subcapitata)
NOEC chronic algae	2.07 mg/l (OECD 201; Pseudokirchneriella subcapitata)

m-phenylenebis(methylamine) (1477-55-0)

LC50 - Fish [1]	87.6 mg/l (OECD 203; Oryzias latipes)
EC50 - Crustacea [1]	15.2 mg/l (OECD 202; Daphnia magna)
ErC50 algae	33.3 mg/l (OECD 201; Pseudokirchneriella subcapitata)
NOEC chronic crustacea	4.7 mg/l (OECD 211; Daphnia magna)
NOEC chronic algae	10.5 mg/l (OECD 201; Pseudokirchneriella subcapitata)

3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)

LC50 - Fish [1]	110 mg/l (EU Method C.1; Leuciscus idus)
EC50 - Crustacea [1]	23 mg/l (OECD 202; Daohnia magna)
ErC50 algae	> 50 mg/l (EU Method C.3; Desmodesmus subspicatus)

salicylic acid (69-72-7)

EC50 - Crustacea [1]	870 mg/l (OECD 202; Daphnia magna)
EC50 72h - Algae [1]	> 100 mg/l (OECD 201; Desmodesmus subspicatus)
NOEC chronic crustacea	10 mg/l (Daphnia magna)

12.2. Persistence and degradability

benzyl alcohol (100-51-6)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer (68609-08-5)

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

m-phenylenebis(methylamine) (1477-55-0)

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

salicylic acid (69-72-7)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

Topcoat E B-component

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

12.3. Bioaccumulative potential

benzyl alcohol (100-51-6)

Partition coefficient n-octanol/water (Log Pow) 1.1 (20 °C)

Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer (68609-08-5)

Partition coefficient n-octanol/water (Log Pow) 2.36 (20 °C)

m-phenylenebis(methylamine) (1477-55-0)

Partition coefficient n-octanol/water (Log Pow) ≈ 0.18 (25 °C; pH 10,3 - 10,4)

3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)

Partition coefficient n-octanol/water (Log Pow) 0.99 (23 °C; pH 6,34)

salicylic acid (69-72-7)

Partition coefficient n-octanol/water (Log Pow) 2.25 (25 °C)

12.4. Mobility in soil

No additional information available.

12.5. Results of PBT and vPvB assessment

Topcoat E B-component

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 08 00 00 - WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS 08 02 00 - wastes from MFSU of other coatings (including ceramic materials) 08 02 99 - wastes not otherwise specified

SECTION 14: Transport information






In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 2735	UN 2735	UN 2735	UN 2735	UN 2735
14.2. UN proper shipping name				
AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : 3-aminomethyl-3,5,5-trimethylcyclohexylamine)	AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : 3-aminomethyl-3,5,5-trimethylcyclohexylamine)	Amines, liquid, corrosive, n.o.s. (CONTAINS : 3-aminomethyl-3,5,5-trimethylcyclohexylamine)	AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : 3-aminomethyl-3,5,5-trimethylcyclohexylamine)	AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : 3-aminomethyl-3,5,5-trimethylcyclohexylamine)
Transport document description				
UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : 3-aminomethyl-3,5,5-trimethylcyclohexylamine), 8, II, (E)	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : 3-aminomethyl-3,5,5-trimethylcyclohexylamine), 8, II	UN 2735 Amines, liquid, corrosive, n.o.s. (CONTAINS : 3-aminomethyl-3,5,5-trimethylcyclohexylamine), 8, II	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : 3-aminomethyl-3,5,5-trimethylcyclohexylamine), 8, II	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : 3-aminomethyl-3,5,5-trimethylcyclohexylamine), 8, II

Topcoat E B-component

Safety Data Sheet


according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

14.3. Transport hazard class(es)				
8	8	8	8	8
				
14.4. Packing group				
II	II	II	II	II
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available.				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: C7
Special provisions (ADR)	: 274
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02
Mixed packing provisions (ADR)	: MP15
Portable tank and bulk container instructions (ADR)	: T11
Portable tank and bulk container special provisions (ADR)	: TP1, TP27
Tank code (ADR)	: L4BN
Vehicle for tank carriage	: AT
Transport category (ADR)	: 2
Hazard identification number (Kemler No.)	: 80
Orange plates	:



Tunnel restriction code (ADR)	: E
EAC code	: 2X
APP code	: B

Transport by sea

Special provisions (IMDG)	: 274
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T11
Tank special provisions (IMDG)	: TP1, TP27
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-B
Stowage category (IMDG)	: A
Segregation (IMDG)	: SGG18, SG35
Properties and observations (IMDG)	: Colourless to yellowish liquids or solutions with a pungent odour. Miscible with or soluble in water. When involved in a fire, evolve toxic gases. Corrosive to most metals, especially to copper and its alloys. Reacts violently with acids. Cause burns to skin, eyes and mucous membranes.

Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y840

Topcoat E B-component

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

PCA limited quantity max net quantity (IATA)	: 0.5L
PCA packing instructions (IATA)	: 851
PCA max net quantity (IATA)	: 1L
CAO packing instructions (IATA)	: 855
CAO max net quantity (IATA)	: 30L
Special provisions (IATA)	: A3, A803
ERG code (IATA)	: 8L

Inland waterway transport

Classification code (ADN)	: C7
Special provisions (ADN)	: 274
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E2
Equipment required (ADN)	: PP, EP
Number of blue cones/lights (ADN)	: 0

Rail transport

Classification code (RID)	: C7
Special provisions (RID)	: 274
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001, IBC02
Mixed packing provisions (RID)	: MP15
Portable tank and bulk container instructions (RID)	: T11
Portable tank and bulk container special provisions (RID)	: TP1, TP27
Tank codes for RID tanks (RID)	: L4BN
Transport category (RID)	: 2
Colis express (express parcels) (RID)	: CE6
Hazard identification number (RID)	: 80

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:		
Reference code	Applicable on	Entry title or description
3(b)	benzyl alcohol ; m-phenylenebis(methylamine) ; 3-aminomethyl-3,5,5-trimethylcyclohexylamine	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	m-phenylenebis(methylamine) ; 3-aminomethyl-3,5,5-trimethylcyclohexylamine	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

No additional information available.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

Topcoat E B-component

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

SECTION 16: Other information

Abbreviations and acronyms:

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ATE	Acute Toxicity Estimate
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LD50	Median lethal dose
PBT	Persistent Bioaccumulative Toxic
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

Data sources : according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179.

Other information : REACH Disclaimer:
This information is based on current knowledge. Consistency of data in the SDS with CSR is considered, as far as the information is available at the time of compilation (cfr Revision date and Version number).
DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H361d	Suspected of damaging the unborn child.

Topcoat E B-component

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Acute Tox. 4 (Oral)	H302	Calculation method
Acute Tox. 4 (Inhalation:dust,mist)	H332	Calculation method
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Repr. 2	H361d	Calculation method
Aquatic Chronic 3	H412	Calculation method

Safety Data Sheet applicable for regions : GB - United Kingdom

The classification complies with : ATP 12

This Safety Data Sheet is compiled by: ChemPros B.V. | +31(0)797676006 | info@chemprosbv.nl