

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Coating PU SG NF Satin Gloss B-component

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use
Use of the substance/mixture : Coating
Product only to be used in combination with component A.

1.2.2. Uses advised against

No additional information available.

1.3. Details of the supplier of the safety data sheet

Quartzline BV
W.A. Boogaerdstraat 5
3316 BN Dordrecht - Nederland
T +31 (0)78 6513100 - F +31 (0)78 6177390
info@quartzline.nl - www.quartzline.nl

1.4. Emergency telephone number

Emergency number : +31 (0)78 6513100
This number is serviced during office hours.

Country	Official advisory body	Address	Emergency number	Remark
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA Belfast	0344 892 0111	Only for the purpose of informing medical personnel in cases of acute intoxications

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (inhalation:dust,mist) Category 4 H332
Skin sensitisation, Category 1 H317
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation H335
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Harmful if inhaled. May cause respiratory irritation. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) :

Warning

Contains :

HDI oligomers, isocyanurate, HDI oligomers, iminooxadiazindione, hexamethylene-diisocyanate, Blocked Polyisocyanate Based on Hexamethylene Diisocyanate (HDI), Hexamethylene diisocyanate, oligomers

Hazard statements (CLP) :

H317 - May cause an allergic skin reaction.
H332 - Harmful if inhaled.
H335 - May cause respiratory irritation.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) :

P261 - Avoid breathing vapours, mist.
P280 - Wear protective gloves, protective clothing, respiratory protection.
P312 - Call doctor, a POISON CENTER if you feel unwell.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.

Coating PU SG NF Satin Gloss B-component

Safety Data Sheet

According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Extra phrases

: Restricted to professional users.
As from 24 August 2023 adequate training is required before industrial or professional use.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc. (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Blocked Polyisocyanate Based on Hexamethylene Diisocyanate (HDI) substance with a Community workplace exposure limit	CAS-No.: 666723-27-9 EC-No.: 679-494-0	50 – 70	Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 3, H412
Hexamethylene diisocyanate, oligomers	CAS-No.: 28182-81-2 EC-No.: 500-060-2 REACH-no: 01-2119488934-20	30 – 50	Acute Tox. 4 (Inhalation), H332 Skin Sens. 1, H317 STOT SE 3, H335
HDI oligomers, isocyanurate	CAS-No.: 28182-81-2 EC-No.: 500-060-2 REACH-no: 01-2119485796-17	< 30	Acute Tox. 4 (Inhalation), H332 Skin Sens. 1, H317 STOT SE 3, H335
HDI oligomers, iminooxadiazindione	EC-No.: 931-297-3 REACH-no: 01-2119488934-20	< 20	Acute Tox. 4 (Inhalation), H332 Skin Sens. 1, H317 STOT SE 3, H335
Cyclohexyldimethylamine	CAS-No.: 98-94-2 EC-No.: 202-715-5 REACH-no: 01-2119533030-60	< 1	Flam. Liq. 3, H226 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1B, H314 Aquatic Chronic 2, H411
hexamethylene-di-isocyanate (Note 2)	CAS-No.: 822-06-0 EC-No.: 212-485-8 EC Index-No.: 615-011-00-1 REACH-no: 01-2119457571-37	< 0,25	Acute Tox. 4 (Oral), H302 Acute Tox. 1 (Inhalation:vapour), H330 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335

Specific concentration limits

Name	Product identifier	Specific concentration limits
hexamethylene-di-isocyanate	CAS-No.: 822-06-0 EC-No.: 212-485-8 EC Index-No.: 615-011-00-1 REACH-no: 01-2119457571-37	(0,5 ≤C < 100) Skin Sens. 1, H317 (0,5 ≤C < 100) Resp. Sens. 1, H334

Note 2 : The concentration of isocyanate stated is the percentage by weight of the free monomer calculated with reference to the total weight of the mixture.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.

Coating PU SG NF Satin Gloss B-component

Safety Data Sheet

According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

First-aid measures after skin contact	: Take off contaminated clothing. Wash skin with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Flush with lukewarm water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Presents no particular fire or explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon oxides (CO, CO ₂).

5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Avoid breathing vapours, mist. Avoid contact with skin and eyes.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Use only outdoors or in a well-ventilated area. Avoid breathing vapours, mist. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	: Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep only in the original container in a cool well ventilated place. Keep container closed when not in use. Store locked up.
Incompatible products	: Strong acids. Strong bases. Strong oxidation agent.
Heat and ignition sources	: Keep away from heat and direct sunlight.

7.3. Specific end use(s)

No additional information available.

Coating PU SG NF Satin Gloss B-component

Safety Data Sheet

According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

Blocked Polyisocyanate Based on Hexamethylene Diisocyanate (HDI) (666723-27-9)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL STEL	0,035 mg/m ³
IOEL STEL [ppm]	0,005 ppm

8.1.2. Recommended monitoring procedures

No additional information available.

8.1.3. Air contaminants formed

No additional information available.

8.1.4. DNEL and PNEC

No additional information available.

8.1.5. Control banding

No additional information available.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

protective clothing. Gloves. Insufficient ventilation: wear respiratory protection.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses. Standard EN 166 - Personal eye-protection - specifications

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing. EN 340

Hand protection:

Wear suitable gloves resistant to chemical penetration. Chemical resistant gloves (according to European standard NF EN 374 or equivalent).

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Gloves	Nitrile rubber (NBR), butyl rubber, Polyvinylchloride (PVC)	6 (> 480 minutes)	>0.11		EN 374

8.2.2.3. Respiratory protection

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. EN 143

Coating PU SG NF Satin Gloss B-component

Safety Data Sheet

According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

Respiratory protection			
Device	Filter type	Condition	Standard
Aerosol mask	Type A - High-boiling (>65 °C) organic compounds, Type P2	Vapour protection, Protection for Liquid particles	EN 143

8.2.2.4. Thermal hazards

No additional information available.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: yellowish.
Odour	: Odourless.
Odour threshold	: No data available.
pH	: No data available.
Relative evaporation rate (butylacetate=1)	: No data available.
Melting point	: No data available.
Freezing point	: No data available.
Boiling point	: No data available.
Flash point	: No data available.
Auto-ignition temperature	: No data available.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: No data available.
Vapour pressure	: No data available.
Relative vapour density at 20 °C	: No data available.
Relative density	: No data available.
Solubility	: No data available.
Partition coefficient n-octanol/water (Log Pow)	: No data available.
Viscosity, kinematic	: No data available.
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.

9.2. Other information

No additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong acids, strong bases and strong oxidants.

10.6. Hazardous decomposition products

Combustion generates: Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Harmful if inhaled.

Coating PU SG NF Satin Gloss B-component

Safety Data Sheet

According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

Coating PU SG NF Satin Gloss B-component	
ATE dust/mist	1,031 mg/l/4h
hexamethylene-di-isocyanate (822-06-0)	
LD50 oral rat	959 mg/kg
LD50 dermal rat	> 7000 mg/kg
LC50 Inhalation - Rat (Vapours)	0,124 mg/l/4h
ATE oral	500 mg/kg bodyweight
ATE vapours	0,124 mg/l/4h
Cyclohexyldimethylamine (98-94-2)	
LD50 oral rat	272 – 289 mg/kg
LD50 dermal rat	380 mg/kg
ATE oral	272 mg/kg bodyweight
ATE dermal	380 mg/kg bodyweight
ATE gases	700 ppmv/4h
ATE vapours	3 mg/l/4h
ATE dust/mist	0,5 mg/l/4h
Hexamethylene diisocyanate, oligomers (28182-81-2)	
LD50 oral rat	> 2000 mg/kg
ATE gases	4500 ppmv/4h
ATE vapours	11 mg/l/4h
ATE dust/mist	1,5 mg/l/4h
HDI oligomers, isocyanurate (28182-81-2)	
LD50 oral rat	> 2500 mg/kg
LD50 dermal rat	> 2000 mg/kg
ATE gases	4500 ppmv/4h
ATE vapours	11 mg/l/4h
ATE dust/mist	1,5 mg/l/4h
Blocked Polyisocyanate Based on Hexamethylene Diisocyanate (HDI) (666723-27-9)	
LD50 oral rat	> 5000 mg/kg
ATE dust/mist	1,5 mg/l/4h
HDI oligomers, iminooxadiazindione	
LD50 oral rat	> 2000 mg/kg
ATE gases	4500 ppmv/4h
ATE vapours	11 mg/l/4h
ATE dust/mist	1,5 mg/l/4h
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.
hexamethylene-di-isocyanate (822-06-0)	
STOT-single exposure	May cause respiratory irritation.

Coating PU SG NF Satin Gloss B-component

Safety Data Sheet

According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

Hexamethylene diisocyanate, oligomers (28182-81-2)	
STOT-single exposure	May cause respiratory irritation.
HDI oligomers, isocyanurate (28182-81-2)	
STOT-single exposure	May cause respiratory irritation.
Blocked Polyisocyanate Based on Hexamethylene Diisocyanate (HDI) (666723-27-9)	
STOT-single exposure	May cause respiratory irritation.
HDI oligomers, iminooxadiazindione	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

Blocked Polyisocyanate Based on Hexamethylene Diisocyanate (HDI) (666723-27-9)	
LC50 - Fish [1]	95,2 mg/l LC50 96 h - Fish [mg/l]
EC50 - Crustacea [1]	> 100 mg/l EC50 48h - Daphnia magna [mg/l]
ErC50 algae	72 mg/l Desmodesmus subspicatus.

12.2. Persistence and degradability

HDI oligomers, isocyanurate (28182-81-2)	
Persistence and degradability	Not readily biodegradable.
HDI oligomers, iminooxadiazindione	
Persistence and degradability	Not readily biodegradable.

12.3. Bioaccumulative potential

No additional information available.

12.4. Mobility in soil

No additional information available.

12.5. Results of PBT and vPvB assessment

Coating PU SG NF Satin Gloss B-component	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

12.6. Other adverse effects

No additional information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
European List of Waste (LoW) code	: 08 00 00 - WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated

Coating PU SG NF Satin Gloss B-component

Safety Data Sheet

According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

ADR	IMDG	IATA	ADN	RID
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available.				

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	Cyclohexyldimethylamine	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	Coating PU SG NF Satin Gloss B-component ; HDI oligomers, isocyanurate ; HDI oligomers, iminooxadiazindione ; hexamethylene-di-isocyanate ; Cyclohexyldimethylamine ; Blocked Polyisocyanate Based on Hexamethylene Diisocyanate (HDI) ; Hexamethylene diisocyanate, oligomers	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	Coating PU SG NF Satin Gloss B-component ; Cyclohexyldimethylamine ; Blocked Polyisocyanate Based on Hexamethylene Diisocyanate (HDI)	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

Coating PU SG NF Satin Gloss B-component

Safety Data Sheet

According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
40.	Cyclohexyldimethylamine	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.
74.	hexamethylene-di-isocyanate	Diisocyanates, O = C=N-R-N = C=O, with R an aliphatic or aromatic hydrocarbon unit of unspecified length

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

No additional information available.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ATE	Acute Toxicity Estimate
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LD50	Median lethal dose
PBT	Persistent Bioaccumulative Toxic
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

Data sources : according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878.

Other information : REACH Disclaimer:
This information is based on current knowledge. Consistency of data in the SDS with CSR is considered, as far as the information is available at the time of compilation (cfr Revision date and Version number). **DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Full text of H- and EUH-statements	
Acute Tox. 1 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 1
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3

Coating PU SG NF Satin Gloss B-component

Safety Data Sheet

According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

Full text of H- and EUH-statements	
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]		
Acute Tox. 4 (Inhalation:dust,mist)	H332	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H335	Calculation method
Aquatic Chronic 3	H412	Calculation method

Safety Data Sheet applicable for regions : GB - United Kingdom

The classification complies with : ATP 12

This Safety Data Sheet is compiled by: ChemPros B.V. | +31(0)797676006 | info@chemprosbv.nl