

EUROSTEP MMA TF

Over concrete or asphalt

Version 1.0 - November 2024

3 layer system applied at 4-6 mm finished off with coloured quartz. System is used in areas which are exposed to mechanical and chemical wear. Designed for environments which need an easy to clean and slip resistant floor.

APPLICATIONS:

- Company kitchens
- Food industry
- Factories
- Carwash
- Fish tanks

ADVANTAGES:

- Aesthetically pleasing
- Fast installation (can be applied up to - 30 degrees Celsius)
- Adjustable level of antislip
- Easy to clean
- Chemical resistance
- Mechanical strength
- Seamless finish
- UV stable quartz and UV stable MMA
- Durable



SYSTEM:

1st layer:	Primer Plex 1120:	0,4 kg/m ²
	Natural quartz 0,4-0,8:	0,6 kg/m ²
2nd layer:	Binder Plex 1510:	0,9 kg/m ²
	Filler for selfleveling Plex filler:	1.8 kg/m ²
	Coloured Quartz QMI 0,4-0,8:	4 kg/m ²
3rd layer:	Topcoat Plex 1690:	0,4 kg/m ²

PROPERTIES:

D SHORE Hardness
D 80

Compressive strength
65 MPa

Bond strength
>1.5 MPa

Temperature resistance
Up to 80°C at 4 mm

Slip resistance
adjustable R9 – R13

